

ABSTRACT

5 An improvement to a code-division-multiple-access (CDMA) system employing spread-spectrum modulation, with the CDMA system having a base station (BS) and a plurality of remote stations. The base station has a BS-spread-spectrum transmitter and a BS-spread-spectrum receiver. A remote station has an RS-spread-spectrum transmitter and an RS-spread-spectrum receiver. The BS transmitter transmits a broadcast common-synchronization channel, which includes a frame-timing signal. The broadcast common-synchronization channel has a common chip-sequence signal, which is common to the plurality of remote stations. In response to the RS-spread-spectrum receiver receiving the broadcast common-synchronization channel, and determining frame timing from the frame-timing signal, an RS-spread-spectrum transmitter transmits an access-burst signal, which includes a plurality of RS-preamble signals, RS-power-control signals, and RS-pilot signals, respectively, transmitted in time, at increasing power levels. The BS-spread-spectrum transmitter, responsive to the BS-spread-spectrum receiver receiving the access-burst signal, and detecting an RS-preamble signal, transmits an acknowledgment signal. In response to the first RS-spread-spectrum receiver receiving the acknowledgment signal, the first RS-spread-spectrum transmitter transmits a spread-spectrum signal having data.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500